

KANGA H Range 3 Tine Rippers, the perfect solution for tackling tough, compacted ground and transforming it into fertile, aerated soil. Engineered specifically for tractors in the 40 to 120hp range, these rippers deliver outstanding performance.

When working on virgin ground, these rippers can be used prior to a Rotary Hoe or Power Harrow. This reduces horsepower requirements, minimises strain on your implements, and decreases the number of passes needed to prepare the soil.

In secondary applications, these rippers excel at breaking up the compacted layer known as the pan, which can develop over time with the use of geared implements. This increases soil moisture retention and enhances crop yields.

Construction

100 x 100 x 9mm square tube main frame, fully welded and reinforced.

3-Point linkage

Category 2. Two-plate, double clevis mount designed to absorb lateral load and decrease metal fatigue.

Removable & adjustable tines

Three bolt-on cast-steel tines are adjustable along the horizontal bar for flexible spacing. Converts to a 2 Tine Ripper by removing centre tine.

Wear parts

Replaceable 'shin' plates covering the most common wear point of the tine. Points are knock-on/knock-off.

Peace of mind

Shear bolt protection with 5,000kg breakout point for extreme impact.

Removable parking stands facilitate connection to tractor.

Code	KRH3-24	KRH3-30
Tine profile	Rigid, bolt-on, 24" Cast Shear Bolt tine	Rigid, bolt-on, 30" Cast Shear Bolt tine
Working depth (max)	610mm	760mm
Weight (kg)	205	220
Tractor range (hp)	40 - 120 33 - 100 @ PTO	60 - 120 50 - 100 @ PTO