

Bale Spike

The KANGA Bale Spike has been designed for farmers, with small to medium horsepower tractors, who are looking for an affordable option to move round hay bales, one at a time. The implement is designed with a small high-tensile spike to stop the bale spinning and a longer, heat-treated Conus II type tine that carries the weight of the bale. The tine is removable and replaceable if the operator wants to purchase different length tines.

The category 1 linkage is a double clevis slip-in-pin design, making the frame less likely to bend or twist with the weight of the bale.

Code	KHH-BS
Construction	Steel 5mm sq. tube, welded and gusseted
Type of tines	Small: 280mm, high-tensile (fixed) Large: 1240mm, straight Conus II (removable)
Weight (kg)	60



Silage Fork

The KANGA Silage Fork has been designed to enable farmers to move a single bale of silage. The implement is a rigid, fully welded and reinforced design with two Conus II bushings welded into the frame. The two tines are made from 60Si7 Alloy Spring Steel (1650 N/mm²) that is forged and heat-treated providing the tines with a maximum load rating of 570N (1578kg/3000lbs).

The category 1 and 2 linkage is a double clevis slip-in-pin design that makes the frame less likely to bend or twist with the weight of the bale.

Code	KHH-SF
Construction	Steel 5mm sq. tube and 12mm plate, welded and gusseted
Type of tines	1240mm, straight Conus II, removable with cone nut
Weight (kg)	87



Adjustable Round Bale Feed Out Fork

The category 1 and 2 linkage KANGA Feed Out Fork is a versatile solution for farmers wanting to handle and distribute round hay bales of various sizes. The adjustable tines accommodate different bale widths, with the flexibility to swap them from side to side.

To feed out, position the bale opposite to its original orientation, lower the linkage to place it on the ground, and slowly drive the tractor forward to unroll the bale. Specially designed pins securely lock in place so they, and the bale, do not separate during feed out.

Code	KHH-FOF
Construction	Steel sq. tube, welded and gusseted
No. of tines	2
Weight (kg)	96

