

The KANGA M Range Post Hole Diggers are suitable for tractors ranging from 30 to 70hp. They are ideal for digging holes for fencing and trees on various properties and applications, including lifestyle and medium-acreage farms, as well as in viticulture and horticultural settings.

Digging holes has never been easier. With the convenience of the tractor's hydraulic 3-point linkage control lever, all the digging can be done from the comfort of the tractor seat. The post hole diggers are easy to disassemble and store in the shed. The optional double-cut head of the auger ensures efficient and rapid digging of deep, clean holes every time.

Code	KPHD50
Gearbox	50hp, 540rpm, 3.18:1 reduction ratio
PTO shaft/clutch	Series 4 with heavy-duty 150mm (6") 40hp friction clutch
Tractor range (hp)	30 - 70 25 - 58 @ PTO
Weight (kg)	135

Connection point

The main frame includes a welded mounting block underneath, featuring three drilled holes to accommodate different tractor linkages.

Boom

Long, 100 x 100 square tube main frame. The 90° join in the main frame is gusseted on both sides and braced on the inside.



3-Point linkage

Category 1. Two-plate, double clevis 'A' frame to increase stability.

Australian-made and sold separately, the double-cut augers are 1.2m in length and, ground conditions permitting, result in hole depths of up to 1.1m. The augers have a replaceable cast-steel fishtail pilot and cast knock-in teeth[#] for faster, more efficient digging.

Code	KPHDA04	KPHDA06	KPHDA09	KPHDA12	KPHDA15	KPHDA18	KPHDA24
Size reference	4" 10cm Auger	6" 15cm Auger	9" 23cm Auger	12" 30cm Auger	15" 38cm Auger	18" 46cm Auger	24" 61cm Auger
Construction	48" (1200mm), double-cutting head, 50mm pipe with 6mm flighting						
Pilot	Replaceable cast steel fishtail design [#]						
Weight (kg)	14	15	20	25	28	35	60

[#] The 100mm (4") model has an oversized fishtail pilot and no teeth due to the size of the auger.