

# S Tine Cultivator



KANGA S Tine Cultivators are versatile secondary cultivation implements, perfect for various tasks such as soil preparation, aeration and weed control. During operation, the 'S' tines of the cultivator vibrate and move in multiple directions – forward, backward and sideways – disturbing the soil, uprooting weeds and burying them.

To enhance overall performance, our S Tine Cultivators come standard with a removable KANGA Crumbler Roller, which further breaks clods. The roller also acts as a height control device, allowing the implement to be run faster, achieving finer cultivation.

When optional sweep points are fitted to the 'S' tines a more significant amount of soil is lifted, mixed and thrown further enhancing the effectiveness of the cultivator.

**Frame**  
Rigid, outer perimeter fabricated from strong, 5mm square steel tube, with 12/16mm front-to-back and lateral reinforcing.

**Crumbler roller**  
Manually height-adjustable. Our unique eight-bar twisted pipe construction features tubes incorporated into the flanges for strength and durability.

**Sealed stub axles**  
Our rollers utilise unique sealed motor vehicle stub axles, highly effective at preventing dirt from entering the bearings. We take pride in the fact that we have never encountered any issues with the rollers we have sold.

**Tines**  
High-tensile spring steel 'S' tines (32 x 12mm) feature a double-ended point (190 x 37mm) reversible and replaceable when worn. Secured by a special clamp, the implement achieves a maximum working depth of 400mm.

**Four rows of tines**  
The adjustable positioning of the tines on the four-row frame minimises trash build-up, ensuring the soil is finely cultivated.

**Options**

**180.405**  
Small sweep point (105mm/4')

**180.406**  
Large sweep point (150mm/6')

Code	KST2.4	KST2.8	KST3.2
Size reference	2.4m   8'0"	2.8m   9'2"	3.2m   10'6"
Linkage	Category 1 & 2, double clevis		Category 2 & 3, double clevis
No. of rows	4		
No. of tines	24	28	32
Overall width (mm)	2750	3150	3550
Working width (mm)	2400	2800	3200
Weight (kg)	425	450	500
Tractor range (hp)	40 - 60   33 - 50 @ PTO	45 - 70   38 - 58 @ PTO	55 - 90   46 - 75 @ PTO