LD RANGE PASTURE HARROW

Suitable for tractors ranging from 15 to 50 horsepower, the KANGA LD Range Pasture Harrow Rakes are a linkage implement designed to support pasture maintenance and manage organic matter. Unlike traditional drag harrows, these implements can be transported easily without damaging roads or tracks. The 2.0m model is rigid, while the 4.0m model folds manually to pass through a standard 2.4m gate.

At the front, a scraping edge lifts clumps of manure, breaks up coarse vegetation and soil clods, and assists with levelling to create a more uniform surface. Behind it, the spiked net section bounces over uneven terrain, helping reduce particle size and spread organic matter evenly across the ground. In some situations, the heavy cast iron star net also lightly scarifies the soil, forming shallow grooves that assist with rainwater capture and moisture penetration.

Manufactured from 3mm tubular steel and braced from front to back, KANGA LD Range Pasture Harrow Rakes are constructed to support structural integrity during use in varied ground conditions. They are commonly used for spreading organic matter and are also suited to rejuvenating outdoor arenas and general landscaping tasks.

Pictured 2.0m rigid harrow (KHPR200)

Harrow material

Three rows of 3-prong, cast iron star net that is reversible. Secured with a shackle, locking bolt/nut.

3-Point linkage

Category 1. Two-plate, double clevis mount. Slotted top link pin hole allowing operators to follow ground contours.

Code	KHPR200	KHPR400
Size reference	2.0m I 6'8" I 80"	4.0m I 13'0" I 156"
Tractor range (hp)	15 - 30 I 12.5 - 25 @ PTO	30 - 50 I 25 - 42 @ PTO
Folds	No, Rigid	Manually
Width (mm)	2000	4000
Fold width (mm)	N/A	2000
Depth (mm)	1300	1500
Weight (kg)	100	245
Price		